NSN 5950-01-046-7479

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-046-7479

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.480 inches single mounting facility single center group and 2.520 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.480 inches single mounting facility single center group and 2.520 inches single mounting facility single center group |
| Frequency Rating: |
| 20.0 kilohertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 3.160 inches |
| Body Width: |
| 3.160 inches |
| Body Height: |
| 3.880 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Thread Size: |
| 0.190 inches single group |
| Winding Operating Current: |
| 42.5 amperes ac single component all secondary |
| Winding Power Rating: |
| 648.9 volts-amperes single component all secondary |
| Winding Operating Voltage: |
| 114.53 ac volts single component single primary |
| Special Features: |
| Current sensing coil on primary terminal |
| Thread Series Designator: |
| Unf single group |
| Terminal Type And Quantity: |
| 4 wire lead and 6 wire lead w/lug |
| Shelf Life: |
| N/a |

--

Unit Of Measure:

NSN 5950-01-046-7479

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0