NSN 5950-01-048-5449

Power Transformer - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5950-01-048-5449



Err.070Reliability Indicator:Not establishedFrequency Rating:400.0 hertz single componentInput-output Phase Relationship:Single phase to single phase single componentBody Length:Between 1.719 inches and 1.781 inchesBody Outside Diameter:0.781 inches single mounting facility single center groupInclosure Type:Hermetically sealedMounting Facility Quantity:3 single groupMunting Method:Threaded stud single groupMinding Function And Quantity:32 single groupHirmary single component and 1 secondary single componentInforacy Qty Per Inch (tpi):32 single groupHirmad Size:0.164 inches single groupWinding Operating Current:2.89 amperes ac single component single secondaryMinding Operating Current:2.600 ac volts single component single secondaryHiread Series Designator:Hiread Series Designator:StorretSturretSturretSturretSturretSturretSturret
Not establishedFrequency Rating:400.0 hertz single componentInput-output Phase Relationship:Single phase to single phase single componentBody Length:Between 1.719 inches and 1.781 inchesBody Outside Diameter:Between 1.969 inches and 2.031 inchesMounting Bolt Circle Diameter:0.781 inches single mounting facility single center groupInclosure Type:Hermetically sealedMounting Facility Quantity:3 single groupMounting Method:1 hreaded stud single groupWinding Function And Quantity:3 single groupMined Size:0.164 inches single groupWinding Operating Current:2.89 amperes ac single component single secondaryMinding Operating Current:26.00 ac volts single component single secondaryMinding Operating Current:26.00 ac volts single component single secondaryWinding Operating Current:26.00 ac volts single component single secondaryWinding Operating Voltage:26.00 ac volts single component single secondaryWinding Operating Voltage:Unc single groupThread Series Designator:Unc single groupTareninal Type And Quantity:5 turret
Frequency Rating:400.0 hertz single componentInput-output Phase Relationship:Single phase to single phase single componentBody Length:Between 1.719 inches and 1.781 inchesBody Outside Diameter:Between 1.969 inches and 2.031 inchesMounting Bolt Circle Diameter:0.781 inches single mounting facility single center groupInclosure Type:Hermetically sealedMounting Method:Threaded stud single groupWinding Function And Quantity:3 single groupThready Qty Per Inch (tpi):32 single groupThread Size:0.164 inches single groupWinding Operating Current:2.89 amperes ac single component single secondaryWinding Operating Voltage:26.00 ac volts single component single secondaryUincing Operating Voltage:Unc single groupThread Series Designator:Unc single groupStorterSingle GroupStorter2.600 ac volts single component single secondarySingle GroupStorterSt
400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Body Length: Between 1.719 inches and 1.781 inches Body Outside Diameter: Between 1.969 inches and 2.031 inches Mounting Bolt Circle Diameter: 0.781 inches single mounting facility single center group Inclosure Type: Hermetically sealed Mounting Facility Quantity: 3 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 2.89 amperes ac single component single secondary Winding Operating Voltage: 26.00 ac volts single component single secondary Unc single group Thread Series Designator: Unc single group
Input-output Phase Relationship:Single phase to single phase single componentBody Length:Between 1.719 inches and 1.781 inchesBody Outside Diameter:Between 1.969 inches and 2.031 inchesMounting Bolt Circle Diameter:0.781 inches single mounting facility single center groupInclosure Type:Hermetically sealedMounting Facility Quantity:3 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:3 single groupSingle groupMined Size:0.164 inches single groupWinding Operating Current:2.89 amperes ac single component single secondaryMinding Operating Voltage:26.00 ac volts single component single secondaryUnc single groupCincead Stude Single groupMinding Operating Voltage:26.00 ac volts single component single secondaryCincead Stude Single component single secondarySingle GroupSingle GroupSingle GroupSingle GroupSingle GroupSingle GroupMinding Operating Voltage:26.00 ac volts single component single secondaryUnc single groupSingle GroupGingle GroupSingle GroupSingle GroupSingle Group </td
Single phase to single phase single component Body Length: Between 1.719 inches and 1.781 inches Body Outside Diameter: Between 1.969 inches and 2.031 inches Mounting Bolt Circle Diameter: 0.781 inches single mounting facility single center group Inclosure Type: Hermetically sealed Mounting Facility Quantity: 3 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 2.89 amperes ac single component single secondary Winding Operating Voltage: 26.00 ac volts single component single secondary Thread Sizes Designator: Unc single group
Body Length:Between 1.719 inches and 1.781 inchesBody Outside Diameter:Between 1.969 inches and 2.031 inchesMounting Bolt Circle Diameter:0.781 inches single mounting facility single center groupInclosure Type:Hermetically sealedMounting Facility Quantity:3 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:1 primary single component and 1 secondary single componentThready Qty Per Inch (tpi):32 single groupMinding Operating Current:2.89 amperes ac single component single secondaryWinding Operating Voltage:26.00 ac volts single component single secondaryUnc single groupThread Stries Designator:Unc single groupStries Designator:Unc single groupSturretSturret
Between 1.719 inches and 1.781 inchesBody Outside Diameter:Between 1.969 inches and 2.031 inchesMounting Bolt Circle Diameter:0.781 inches single mounting facility single center groupInclosure Type:Hermetically sealedMounting Facility Quantity:3 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:1 primary single component and 1 secondary single componentThready Qty Per Inch (tpi):32 single groupThread Size:0.164 inches single groupWinding Operating Current:2.89 amperes ac single component single secondaryWinding Operating Voltage:26.00 ac volts single component single secondaryUnc single groupThread Series Designator:Unc single groupTureat Sure Designator:Unc single group
Body Outside Diameter: Between 1.969 inches and 2.031 inches Mounting Bolt Circle Diameter: 0.781 inches single mounting facility single center group Inclosure Type: Hermetically sealed Mounting Facility Quantity: 3 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 2.89 amperes ac single component single secondary Winding Operating Voltage: 26.00 ac volts single component single secondary Thread Size Designator: Unc single group
Between 1.969 inches and 2.031 inchesMounting Bolt Circle Diameter:0.781 inches single mounting facility single center groupInclosure Type:Hermetically sealedMounting Facility Quantity:3 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:1 primary single component and 1 secondary single componentThready Qty Per Inch (tpi):32 single groupThread Size:0.164 inches single groupWinding Operating Current:2.89 amperes ac single component single secondaryWinding Operating Current:26.00 ac volts single component single secondaryInread Series Designator:Unc single groupTerminal Type And Quantity:5 turret
Mounting Bolt Circle Diameter: 0.781 inches single mounting facility single center group Inclosure Type: Hermetically sealed Mounting Facility Quantity: 3 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 2.89 amperes ac single component single secondary Winding Operating Voltage: 26.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 turret
0.781 inches single mounting facility single center group Inclosure Type: Hermetically sealed Mounting Facility Quantity: 3 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 2.89 amperes ac single component single secondary Winding Operating Voltage: 26.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 turret
Inclosure Type: Hermetically sealed Mounting Facility Quantity: 3 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 2.89 amperes ac single component single secondary Winding Operating Voltage: 26.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 turret
Hermetically sealed Mounting Facility Quantity: 3 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 2.89 amperes ac single component single secondary Winding Operating Voltage: 26.00 ac volts single component single secondary Unc single group Thread Series Designator: Unc single group 5 turret
Mounting Facility Quantity:3 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:1 primary single component and 1 secondary single componentThready Qty Per Inch (tpi):32 single groupThread Size:0.164 inches single groupWinding Operating Current:2.89 amperes ac single component single secondaryWinding Operating Voltage:26.00 ac volts single component single secondaryThread Series Designator:Unc single groupTerminal Type And Quantity:5 turret
3 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 2.89 amperes ac single component single secondary Winding Operating Voltage: 26.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 turret
Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 2.89 amperes ac single component single secondary Winding Operating Voltage: 26.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 turret
Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 2.89 amperes ac single component single secondary Winding Operating Voltage: 26.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 turret
 Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 2.89 amperes ac single component single secondary Winding Operating Voltage: 26.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 turret
 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 2.89 amperes ac single component single secondary Winding Operating Voltage: 26.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 turret
 Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 2.89 amperes ac single component single secondary Winding Operating Voltage: 26.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 turret
 32 single group Thread Size: 0.164 inches single group Winding Operating Current: 2.89 amperes ac single component single secondary Winding Operating Voltage: 26.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 turret
Thread Size: 0.164 inches single group Winding Operating Current: 2.89 amperes ac single component single secondary Winding Operating Voltage: 26.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 turret
 0.164 inches single group Winding Operating Current: 2.89 amperes ac single component single secondary Winding Operating Voltage: 26.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 turret
 Winding Operating Current: 2.89 amperes ac single component single secondary Winding Operating Voltage: 26.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 turret
 2.89 amperes ac single component single secondary Winding Operating Voltage: 26.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 turret
Winding Operating Voltage: 26.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 turret
 26.00 ac volts single component single secondary Thread Series Designator: Unc single group Terminal Type And Quantity: 5 turret
Thread Series Designator: Unc single group Terminal Type And Quantity: 5 turret
Unc single group Terminal Type And Quantity: 5 turret
Terminal Type And Quantity: 5 turret
5 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A058b0