NSN 5950-01-048-9313

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-048-9313

| Deliahility Indicator |
|--|
| Reliability Indicator: |
| Not established Contact To Contact Distance Between Mounting Escilities Berellel To Longth: |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.810 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.380 inches single mounting facility single center group |
| Mounting Slot Width: |
| 0.200 inches single group |
| Frequency Rating: |
| 50.0 hertz single component and 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 3.770 inches |
| Body Width: |
| 3.380 inches |
| Body Height: |
| 3.000 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and slot single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Voltage: |
| 440.00 ac volts single component single primary and 460.00 ac volts single component single primary and 480.00 ac volts single |
| component single primary |
| Terminal Type And Quantity: |
| 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |