

View Online at <https://aerobasegroup.com/nsn/5950-01-049-8443>

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.220 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.152 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

4.620 inches

Body Width:

3.400 inches

Body Height:

2.000 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 9 secondary single component

Winding Operating Current:

5.3 amperes ac single component 2nd secondary

Winding Power Rating:

490.0 volts-amperes single component single primary

Winding Operating Voltage:

9.90 ac pounds per hour wet single component 4th secondary

Special Features:

5th secondary 12.5v, 0.2a; 6th 24.0v, 204ma; 7th 25.8v, 204ma; 8th 18.9v, 816ma; 9th 17.1v, 816ma

Terminal Type And Quantity:

31 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0