

View Online at <https://aerobasegroup.com/nsn/5950-01-050-3936>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

3.120 inches

Body Width:

2.620 inches

Body Height:

2.250 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

60.0 milliamperes dc single component 1st secondary

Winding Operating Voltage:

44.00 dc volts single component 1st secondary

Special Features:

Voltage readings taken after going through diodes on output of transformer; current readings were taken using same procedure

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0