

View Online at <https://aerobasegroup.com/nsn/5950-01-051-1286>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.125 inches single mounting facility single center group

**Mounting Slot Width:**

0.187 inches single group

**Frequency Rating:**

45.0 hertz single component and 440.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

**Body Length:**

3.750 inches

**Body Width:**

2.750 inches

**Body Height:**

4.500 inches

**Inclosure Type:**

Partially enclosed, double shell

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Flange single group and slot single group

**Winding Function And Quantity:**

2 primary single component and 5 secondary single component

**Winding Operating Current:**

9.3 amperes ac single component 1st secondary

**Winding Operating Voltage:**

22.00 ac volts single component 4th secondary

**Special Features:**

2primary windings; 5secondary windings

**Terminal Type And Quantity:**

17 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0