

View Online at <https://aerobasegroup.com/nsn/5950-01-051-3335>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches single mounting facility single center group

Mounting Slot Width:

0.281 inches single group

Frequency Rating:

47.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Maximum Transformer Power Rating:

11.0 decibels single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

9.120 inches

Body Width:

7.000 inches

Body Height:

5.120 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

1.5 amperes ac single component single secondary

Winding Operating Voltage:

440.00 ac volts single component single primary

Terminal Type And Quantity:

7 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0