NSN 5950-01-053-5095

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-053-5095

| Reliability Indicator: |
|---|
| Not established |
| Overall Length: |
| 1.940 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.210 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.980 inches single mounting facility single center group |
| Overall Width: |
| 1.610 inches |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Maximum Operating Temp: |
| 121.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.164 inches single group |
| Winding Operating Voltage: |
| 115.00 ac pounds per hour wet single component single primary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |
| |