

View Online at <https://aerobasegroup.com/nsn/5950-01-053-8434>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Frequency Rating:

57.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

4.625 inches

Body Width:

4.000 inches

Body Height:

4.812 inches

End Application:

Atcbi-5

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

3.9 amperes ac single component 2nd secondary

Winding Power Rating:

43.7 volts-amperes single component 1st secondary

Winding Operating Voltage:

28.00 ac volts single component 2nd secondary

Special Features:

Function: transformer, power; reference data: 1a3t201, ti 6360.70, fa 9400, pg 8-35

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

13 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0