

View Online at <https://aerobasegroup.com/nsn/5950-01-055-8474>

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

7.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.000 inches single mounting facility single center group

**Mounting Hole Diameter:**

0.281 inches single group

**Frequency Rating:**

1000.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

9.750 inches

**Body Width:**

6.180 inches

**End Application:**

Arsr-3, p/o final power amplifier

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Flange single group and unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Current:**

14.0 amperes ac single component single secondary

**Winding Power Rating:**

308.0 volts-amperes single component single secondary

**Winding Operating Voltage:**

48.00 ac volts single component single primary

**Special Features:**

Function: transformer, filament; reference data: 8t2, ti-6340.8 arsr-3 system, part ii, sec 8, vol 9, pg 8-564

**Terminal Type And Quantity:**

3 terminal block w/screws and 2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0