

View Online at <https://aerobasegroup.com/nsn/5950-01-055-8474>

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.281 inches single group

Frequency Rating:

1000.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

9.750 inches

Body Width:

6.180 inches

End Application:

Arsr-3, p/o final power amplifier

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

14.0 amperes ac single component single secondary

Winding Power Rating:

308.0 volts-amperes single component single secondary

Winding Operating Voltage:

48.00 ac volts single component single primary

Special Features:

Function: transformer, filament; reference data: 8t2, ti-6340.8 arsr-3 system, part ii, sec 8, vol 9, pg 8-564

Terminal Type And Quantity:

3 terminal block w/screws and 2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0