NSN 5950-01-057-0516

Pulse Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-057-0516

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

8.550 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

8.550 inches single mounting facility single center group

Overall Height:

11.000 inches

Mounting Hole Diameter:

0.213 inches single group

Frequency Rating:

1.0 kilohertz single component

Primary To Secondary Turn Ratio:

1 to 9 single component

Pulse Repetition Rate:

1.2 kilohertz single component

Winding Shielding Method:

External inclosure single component

Body Length:

9.000 inches

Body Width:

9.000 inches

Maximum Operating Temp:

105.0 degrees celsius

End Application:

An/gpn20

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

47.0 amperes ac single component all secondary

Dc Resistance Rating In Ohms:

0.250 single component all secondary

Terminal Type And Quantity:

3 standoff insulator and 3 standoff, solder lug

Shelf Life:

N/a

NSN 5950-01-057-0516

Pulse Transformer - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0