## NSN 5950-01-057-3240

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-057-3240

| Reliability Indicator:  |
|---|
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 5.000 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 2.375 inches single mounting facility single center group                 |
| Mounting Hole Diameter:   |
| 0.281 inches single group   |
| Frequency Rating:   |
| 60.0 hertz single component   |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Body Length:  |
| 7.000 inches  |
| Body Width:   |
| 7.000 inches  |
| Body Height:  |
| 5.188 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Unthreaded hole single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component               |
| Winding Operating Current:  |
| 5.0 amperes ac single component single secondary                          |
| Winding Operating Voltage:  |
| 440.00 ac volts single component single primary                           |
| Terminal Type And Quantity:   |
| 4 wire lead   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A058b0  |