

View Online at <https://aerobasegroup.com/nsn/5950-01-057-5040>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.200 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.900 inches single mounting facility single center group

Frequency Rating:

480.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component and three phase to six phase single component

Transformer Winding Connection Type:

Delta-wye

Maximum Transformer Power Rating:

352.3 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to inclosure and brought out to terminal single component

Body Length:

4.800 inches

Body Width:

2.500 inches

Body Height:

3.440 inches

Maximum Operating Temp:

125.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

6.0 amperes ac single component 3rd secondary

Winding Power Rating:

90.0 volts-amperes single component 1st secondary

Winding Operating Voltage:

26.00 ac volts single component 1st secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

18 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0