## NSN 5950-01-057-5530

Power Autotransformer Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-01-057-5530             |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.750 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 2.250 inches single mounting facility single center group                 |
| Mounting Hole Diameter:   |
| 0.218 inches single group and 0.228 inches single group                   |
| Frequency Rating:   |
| 400.0 hertz single component  |
| Input-output Phase Relationship:  |
| Single phase to single phase single component                             |
| Winding Shielding Method:   |
| External inclosure single component                                       |
| Body Length:  |
| 4.125 inches  |
| Body Width:   |
| 2.750 inches  |
| Body Height:  |
| 2.750 inches  |
| Maximum Operating Temp:   |
| 130.0 degrees celsius   |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Flange single group and unthreaded hole single group                      |
| Winding Function And Quantity:  |
| 1 primary, fixed autotransformer type single component                    |
| Winding Operating Current:  |
| 12.0 amperes ac single component single primary output                    |
| Terminal Type And Quantity:   |
| 4 threaded stud   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |

Fiig:

A058b0