

View Online at <https://aerobasegroup.com/nsn/5950-01-057-6838>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.219 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.880 inches single mounting facility single center group

Mounting Slot Width:

0.220 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

2.560 inches

Body Width:

2.400 inches

Body Height:

2.810 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Bracket single group and slot single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Winding Operating Current:

400.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

6.00 ac pounds per hour wet single component 3rd secondary

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0