

View Online at <https://aerobasegroup.com/nsn/5950-01-058-7723>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.234 inches single mounting facility all center groupings and 3.266 inches single mounting facility all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.320 inches single mounting facility all center groupings and 2.440 inches single mounting facility all center groupings

Overall Height:

Between 5.344 inches and 5.406 inches

Mounting Slot Width:

0.156 inches all groupings

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-delta

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

3.800 inches

Body Width:

3.015 inches

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 all groupings

Mounting Method:

Slot all groupings

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Winding Operating Current:

9.1 amperes dc single component 2nd secondary

Winding Operating Voltage:

20.30 ac volts single component 4th secondary

Special Features:

One primary winding; five secondary windings

Terminal Type And Quantity:

20 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0