## NSN 5950-01-058-9735

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-058-9735

Reliability	Indicator:
-------------	------------

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

2.940 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.000 inches single mounting facility single center group

## **Mounting Hole Diameter:**

0.156 inches single group

## **Frequency Rating:**

48.0 hertz single component and 440.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Body Length:**

3.250 inches

#### **Body Width:**

2.560 inches

#### **Body Height:**

3.060 inches

## **End Application:**

Oliver perry class ffg, forrestal class cv, los angeles class ssn (688), kidd class ddg, virginia class cgn (41), spruance class dd (963), tarawa class lha, sturgeon class ssn (637). Mx peacekeeper missle support equipment.

## Inclosure Type:

Fully enclosed

### **Mounting Facility Quantity:**

4 single group

## **Mounting Method:**

Flange single group and unthreaded hole single group

## **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

#### **Winding Operating Current:**

2.85 amperes ac single component single secondary

## **Winding Power Rating:**

49.8 volts-amperes single component single secondary

## **Criticality Code Justification:**

Feat

## Winding Operating Voltage:

17.50 ac volts single component single secondary

## **Special Features:**

Weapon systen essential

#### **Terminal Type And Quantity:**

8 wire lead

#### Shelf Life:

N/a

# NSN 5950-01-058-9735

Power Transformer - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A058b0