

View Online at <https://aerobasegroup.com/nsn/5950-01-058-9735>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.940 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.156 inches single group

Frequency Rating:

48.0 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.250 inches

Body Width:

2.560 inches

Body Height:

3.060 inches

End Application:

Oliver perry class ffg, forrestal class cv, los angeles class ssn (688), kidd class ddg, virginia class cgn (41), spruance class dd (963), tarawa class lha, sturgeon class ssn (637). Mx peacekeeper missile support equipment.

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

2.85 amperes ac single component single secondary

Winding Power Rating:

49.8 volts-amperes single component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

17.50 ac volts single component single secondary

Special Features:

Weapon system essential

Terminal Type And Quantity:

8 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0