

View Online at <https://aerobasegroup.com/nsn/5950-01-060-4911>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.969 inches single mounting facility single center group and 3.031 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.407 inches single mounting facility single center group and 2.469 inches single mounting facility single center group

Overall Height:

Between 4.562 inches and 4.874 inches

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

Between 3.813 inches and 3.938 inches

Body Width:

Between 3.250 inches and 3.375 inches

Body Height:

Between 4.124 inches and 4.312 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Voltage:

6.50 ac volts single component 1st secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0