

View Online at <https://aerobasegroup.com/nsn/5950-01-061-0940>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

3.000 inches

Body Width:

2.500 inches

Body Height:

1.500 inches

Maximum Operating Temp:

105.0 degrees celsius

End Application:

Aircraft, thunderbolt ii, a-10; aircraft, orion p-3

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

40 single group

Thread Size:

0.112 inches single group

Winding Operating Current:

750.0 milliamperes ac single component 4th secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

9.50 ac volts single component 4th secondary

Special Features:

Weapon system essential

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0