

View Online at <https://aerobasegroup.com/nsn/5950-01-061-1529>

Reliability Indicator:

Not established

Overall Length:

2.400 inches

Mounting Hole Diameter:

0.200 inches single group

Frequency Rating:

50.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

2.9 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

1.620 inches

Body Width:

1.800 inches

Body Height:

2.100 inches

Maximum Operating Temp:

55.0 degrees celsius

Distance Between Mounting Facility Centers:

2.000 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

25.0 milliamperes ac single component 2nd secondary

Winding Power Rating:

1.7 volts-amperes single component 2nd secondary

Winding Operating Voltage:

6.00 ac volts single component 1st secondary

Special Features:

One terminal common to both secondary windings

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0