## NSN 5950-01-061-1530

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-061-1530
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.680 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.125 inches single mounting facility single center group
Mounting Slot Width:
0.203 inches single group
Frequency Rating:
2.0 kilohertz single component and 2.5 kilohertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
4.380 inches
Body Width:
3.250 inches
Body Height:
3.500 inches
End Application:
Radio set (a1815) (an/grc-193), airborne mobile dir air spt ctl (2id), (02m jul83)(an/uyq-3a)
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and slot single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Winding Operating Current:
600.0 milliamperes ac single component single secondary
Criticality Code Justification:
Feat
Winding Operating Voltage:
54.00 ac volts single component single primary
Special Features:
Weapon system essential
Terminal Type And Quantity:
5 wire lead
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5950-01-061-1530

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0