## NSN 5950-01-061-5899

Power Transformer - Page 1 of 2

Reliability Indicator:



View Online at https://aerobasegroup.com/nsn/5950-01-061-5899

To Length:

To Width:

Not established
Center To Center Distance Between Mounting Facilities Parallel
5.000 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel
4.000 inches single mounting facility single center group
Frequency Rating:
47.0 hertz single component and 63.0 hertz single component
Input-output Phase Relationship:
Three phase to three phase single component
Winding Shielding Method:
Internal shield grounded to inclosure single component
Body Length:
5.000 inches
Body Width:
5.000 inches
Body Height:
4.500 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 4 secondary single component
Thready Qty Per Inch (tpi):
20 single group
Thread Size:
0.250 inches single group
Winding Operating Current:
1.1 amperes ac single component 3rd secondary
Winding Operating Voltage:
8.00 ac volts single component 1st secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
21 solder stud
Shelf Life:
N/a
Unit Of Measure:

## NSN 5950-01-061-5899

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0