

View Online at <https://aerobasegroup.com/nsn/5950-01-062-1563>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.000 inches single mounting facility single center group

Frequency Rating:

57.0 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

5.500 inches

Body Width:

5.000 inches

Body Height:

6.500 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Current:

5.5 amperes dc single component single secondary

Winding Operating Voltage:

54.00 ac volts single component 1st secondary

Special Features:

Second secondary connected to regulate the capacitor

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0