

View Online at <https://aerobasegroup.com/nsn/5950-01-063-9191>

Reliability Indicator:

Not established

Inductance Rating:

0.15 microhenries single component single winding

Coil Form Type:

Solid single component

Core Construction:

Solid single component

Body Length:

Between 0.365 inches and 0.385 inches

Body Outside Diameter:

Between 0.145 inches and 0.165 inches

Maximum Operating Temp:

90.0 degrees celsius

End Application:

Ticonderoga class cg (47); support equipment, b-52 aircraft; sturgeon class ssn (637); los angeles class ssn (688); engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); nimitz class cvn; landing craft air cushion (lcac); forrestal class cv; spruance class dd (963)

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Rating Method:

Electrical single component single winding

Features Provided:

Tinned wire leads

Winding Operating Current:

2.45 amperes dc single component single winding

Dc Resistance Rating In Ohms:

0.030 single component single winding

Quality Factor:

50 single component single winding

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0