

View Online at <https://aerobasegroup.com/nsn/5950-01-064-0524>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.100 inches single mounting facility single center group and 3.140 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.230 inches single mounting facility single center group and 2.270 inches single mounting facility single center group

Mounting Slot Width:

0.180 inches single group and 0.220 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

3.880 inches

Body Width:

2.880 inches

Body Height:

Between 3.160 inches and 3.200 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

3.5 amperes dc single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single primary

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0