

View Online at <https://aerobasegroup.com/nsn/5950-01-064-9276>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.295 inches single mounting facility single center group and 3.325 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.235 inches single mounting facility single center group and 2.265 inches single mounting facility single center group

**Mounting Slot Width:**

0.188 inches single group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

Between 3.735 inches and 3.765 inches

**Body Width:**

Between 2.795 inches and 2.825 inches

**Body Height:**

Between 3.365 inches and 3.395 inches

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Slot single group

**Winding Function And Quantity:**

1 primary single component and 5 secondary single component

**Winding Operating Current:**

7.0 amperes ac single component 1st secondary

**Winding Operating Voltage:**

73.15 ac volts single component 4th secondary and 80.85 ac volts single component 4th secondary

**Special Features:**

1primary, 5 secondary windings

**Terminal Type And Quantity:**

12 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0