

View Online at <https://aerobasegroup.com/nsn/5950-01-064-9276>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.295 inches single mounting facility single center group and 3.325 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.235 inches single mounting facility single center group and 2.265 inches single mounting facility single center group

Mounting Slot Width:

0.188 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

Between 3.735 inches and 3.765 inches

Body Width:

Between 2.795 inches and 2.825 inches

Body Height:

Between 3.365 inches and 3.395 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Winding Operating Current:

7.0 amperes ac single component 1st secondary

Winding Operating Voltage:

73.15 ac volts single component 4th secondary and 80.85 ac volts single component 4th secondary

Special Features:

1primary, 5 secondary windings

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0