

View Online at <https://aerobasegroup.com/nsn/5950-01-065-4549>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.926 inches single mounting facility single center group and 5.966 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.224 inches single mounting facility single center group and 2.264 inches single mounting facility single center group

Frequency Rating:

25.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

1.5 kilovolt-ampere single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

6.550 inches

Body Width:

2.380 inches

Body Height:

2.380 inches

Maximum Operating Temp:

71.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Features Provided:

W/overload protection

Thread Size:

0.164 inches single group

Winding Operating Current:

100.0 microamperes ac single component single secondary

Winding Operating Voltage:

13.79 ac volts single component single primary

Special Features:

1 connector is for high voltage hook up

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

2 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0