

View Online at <https://aerobasegroup.com/nsn/5950-01-065-8053>

Reliability Indicator:

Not established

Overall Length:

Between 4.480 inches and 4.520 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.730 inches single mounting facility single center group and 3.770 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.980 inches single mounting facility single center group and 3.020 inches single mounting facility single center group

Overall Height:

4.500 inches

Overall Width:

Between 3.730 inches and 3.770 inches

Mounting Hole Diameter:

0.250 inches single group

Frequency Rating:

48.0 hertz single component and 62.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Features Provided:

Color coded lead

Winding Operating Current:

4.0 amperes dc single component 2nd secondary

Winding Power Rating:

89.0 volts-amperes single component 1st secondary

Winding Operating Voltage:

8.90 dc volts single component 1st secondary

Terminal Type And Quantity:

2 tab, solder lug and 8 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0