## NSN 5950-01-065-8406

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-065-8406

Reliability Indicator:
Not established
Mounting Hole Diameter:
0.188 inches single group
Frequency Rating:
50.0 hertz single component or 60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield brought out to terminal single component
Body Length:
7.000 inches
Body Width:
4.000 inches
Body Height:
2.000 inches
Distance Between Mounting Facility Centers:
0.750 inches single mounting facility single center group and 2.500 inches single mounting facility single center group
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
2 primary single component and 3 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.164 inches single group
Winding Operating Current:
2.6 amperes ac single component 1st secondary
Winding Operating Voltage:
8.30 ac volts single component 1st secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
15 pin
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5950-01-065-8406

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0