

View Online at <https://aerobasegroup.com/nsn/5950-01-067-0999>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.490 inches single mounting facility all center groupings and 2.510 inches single mounting facility all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.177 inches single mounting facility all center groupings and 1.197 inches single mounting facility all center groupings

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-delta

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 3.020 inches and 3.060 inches

Body Width:

Between 1.710 inches and 1.750 inches

Body Height:

Between 2.830 inches and 2.870 inches

Maximum Operating Temp:

100.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 all groupings

Mounting Method:

Threaded hole all groupings

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Thread Size:

0.138 inches all groupings

Winding Operating Current:

600.0 milliamperes ac single component 4th secondary

Winding Power Rating:

82.8 volts-amperes single component 3rd secondary

Winding Operating Voltage:

9.13 ac volts single component 1st secondary

Special Features:

One primary winding; five secondary windings

Thread Series Designator:

Unc all groupings

Terminal Type And Quantity:

20 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0