

View Online at <https://aerobasegroup.com/nsn/5950-01-068-2711>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.120 inches single mounting facility single center group

Mounting Slot Width:

0.280 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-wye

Winding Shielding Method:

Internal shield grounded to core and mounting single component

Body Length:

6.250 inches

Body Width:

4.120 inches

Body Height:

4.660 inches

Maximum Operating Temp:

100.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

5.8 amperes ac single component 3rd secondary

Winding Operating Voltage:

21.10 ac volts single component all secondary

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0