NSN 5950-01-068-5167

Reactor - Page 1 of 2

Reliability Indicator:

N/a



View Online at https://aerobasegroup.com/nsn/5950-01-068-5167

| Not established |
|---|
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.313 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.688 inches single mounting facility single center group |
| Inductance Type: |
| Fixed |
| Inductance Rating: |
| 200.00 millihenries single component single winding |
| Frequency Rating: |
| 120.0 hertz single component |
| Body Length: |
| 4.313 inches |
| Body Width: |
| 3.688 inches |
| Body Height: |
| 4.500 inches |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Rating Method: |
| Electrical single component single winding |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.190 inches single group |
| Winding Operating Current: |
| 250.0 milliamperes dc single component single winding |
| Dc Resistance Rating In Ohms: |
| 0.700 single component single winding |
| Thread Series Designator: |
| Unf single group |
| Terminal Type And Quantity: |
| 2 threaded stud |
| Shelf Life: |

NSN 5950-01-068-5167

Reactor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A058b0