NSN 5950-01-068-5170

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-068-5170

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.166 inches single group

Frequency Rating:

2.2 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

3.812 inches

Body Width:

3.812 inches

Body Height:

1.750 inches

Maximum Operating Temp:

90.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Winding Operating Current:

750.0 milliamperes ac single component 4th secondary

Winding Operating Voltage:

66.00 ac volts single component 2nd secondary

Terminal Type And Quantity:

16 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5950-01-068-5170

Power Transformer - Page 2 of 2

Fiig: A058b0

