

View Online at <https://aerobasegroup.com/nsn/5950-01-069-4833>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Frequency Rating:

47.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

3.875 inches

Body Width:

3.062 inches

Body Height:

3.500 inches

Maximum Operating Temp:

75.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

1.0 amperes ac single component all secondary

Winding Operating Voltage:

39.00 ac volts single component 2nd secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0