

View Online at <https://aerobasegroup.com/nsn/5950-01-069-6072>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.875 inches single mounting facility single center group

Mounting Slot Width:

0.156 inches single group

Frequency Rating:

380.0 hertz single component and 500.0 hertz single component

Input-output Phase Relationship:

Three phase to six phase single component

Transformer Winding Connection Type:

Delta-wye

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

4.781 inches

Body Width:

3.020 inches

Body Height:

3.688 inches

Maximum Operating Temp:

60.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

8.2 amperes ac single component single secondary

Winding Power Rating:

45.1 volts-amperes single component single secondary

Winding Operating Voltage:

5.50 ac volts single component single secondary

Terminal Type And Quantity:

8 pin and 3 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0