

View Online at <https://aerobasegroup.com/nsn/5950-01-069-6074>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

4.406 inches

Body Width:

3.906 inches

Body Height:

2.031 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

50.0 milliamperes ac single component 4th secondary

Winding Operating Voltage:

28.50 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0