

View Online at <https://aerobasegroup.com/nsn/5950-01-069-8644>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.249 inches single mounting facility single center group and 1.279 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.170 inches single mounting facility single center group and 1.200 inches single mounting facility single center group

Overall Height:

2.677 inches

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.839 inches

Body Width:

1.630 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

310.0 milliamperes ac single component single secondary

Winding Power Rating:

35.7 volts-amperes single component single secondary

Winding Operating Voltage:

58.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0