## NSN 5950-01-070-5898

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-070-5898

| Reliability Indicator:  |
|---|
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.375 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 2.250 inches single mounting facility single center group                 |
| Mounting Slot Width:  |
| 0.203 inches single group   |
| Frequency Rating:   |
| 720.0 hertz single component  |
| Body Length:  |
| 3.562 inches  |
| Body Width:   |
| 3.000 inches  |
| Body Height:  |
| 3.000 inches  |
| Winding Quantity:   |
| 1 single component  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Slot single group   |
| Rating Method:  |
| Electrical single component single winding                                |
| Winding Operating Current:  |
| 75.0 amperes dc single component single winding                           |
| Dc Resistance Rating In Ohms:   |
| 0.005 single component single winding                                     |
| Terminal Type And Quantity:   |
| 3 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| Δ058b0  |