NSN 5950-01-070-5899

Audio Frequency Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-070-5899

| Reliability Indicator: |
|--|
| Not established |
| Impedance Rating In Ohms: |
| 800.0 single component single secondary and 1200.0 single component single secondary |
| Frequency Rating: |
| 300.0 hertz single component and 20.0 kilohertz single component |
| Maximum Transformer Power Rating: |
| 50.0 milliwatts single component |
| Primary To Secondary Turn Ratio: |
| 1 to 1 single component |
| Body Length: |
| 0.469 inches |
| Body Outside Diameter: |
| 0.344 inches |
| Maximum Operating Temp: |
| 105.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Terminal single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Current: |
| 500.0 microamperes dc single component single primary |
| Test Data Document: |
| 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 6 wire lead |
| Specification Data: |
| 81349-mil-t-27/172 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| Δ058h0 |