

View Online at <https://aerobasegroup.com/nsn/5950-01-070-8005>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Overall Height:

3.280 inches

Frequency Rating:

360.0 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Three phase to six phase single component and three phase to three phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

5.380 inches

Body Width:

2.940 inches

Body Height:

2.940 inches

Maximum Operating Temp:

85.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

0.2 amperes ac single component single primary

Winding Power Rating:

23.0 volts-amperes single component single primary

Winding Operating Voltage:

7.60 ac volts single component 1st secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

20 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0