## NSN 5950-01-071-3210

Reliability Indicator:

Radio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-071-3210

| Not established   |
|---|
| Turn Quantity:  |
| 196 single component all primary  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.000 inches single mounting facility single center group                 |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 3.875 inches single mounting facility single center group                 |
| Frequency Rating:   |
| 400.0 hertz single component  |
| Coil Form Type:   |
| Solid single component  |
| Body Length:  |
| 4.875 inches  |
| Body Width:   |
| 2.562 inches  |
| Body Height:  |
| 4.125 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Bracket single group and threaded hole single group                       |
| Rating Method:  |
| Winding turns single component all secondary                              |
| Winding Function And Quantity:  |
| 2 primary single component and 2 secondary single component               |
| Thready Qty Per Inch (tpi):   |
| 32 single group   |
| Thread Size:  |
| 0.164 inches single group   |
| Winding Conductor Size:   |
| 0.07196 inches american wire gage single component all secondary          |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 12 tab, solder lug  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |

## NSN 5950-01-071-3210

Radio Frequency Transformer - Page 2 of 2



| em |  |  |  |
|----|--|--|--|
|    |  |  |  |
|    |  |  |  |

No

Fiig:

A058b0