

View Online at <https://aerobasegroup.com/nsn/5950-01-071-4660>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

3.433 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.422 inches single mounting facility single center group and 2.452 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.296 inches single mounting facility single center group and 2.326 inches single mounting facility single center group

**Overall Height:**

4.213 inches

**Overall Width:**

3.315 inches

**Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Maximum Operating Temp:**

65.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Size:**

0.250 inches single group

**Winding Operating Current:**

65.0 milliamperes ac single component single primary

**Winding Power Rating:**

72.0 volts-amperes single component single secondary

**Winding Operating Voltage:**

8.00 ac volts single component single secondary and 12.00 ac volts single component single secondary and 16.00 ac volts single component single secondary and 20.00 ac volts single component single secondary and 24.00 ac volts single component single secondary

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

10 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0