

View Online at <https://aerobasegroup.com/nsn/5950-01-071-4660>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

3.433 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.422 inches single mounting facility single center group and 2.452 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.296 inches single mounting facility single center group and 2.326 inches single mounting facility single center group

Overall Height:

4.213 inches

Overall Width:

3.315 inches

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Maximum Operating Temp:

65.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

65.0 milliamperes ac single component single primary

Winding Power Rating:

72.0 volts-amperes single component single secondary

Winding Operating Voltage:

8.00 ac volts single component single secondary and 12.00 ac volts single component single secondary and 16.00 ac volts single component single secondary and 20.00 ac volts single component single secondary and 24.00 ac volts single component single secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

10 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0