

View Online at <https://aerobasegroup.com/nsn/5950-01-072-3976>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.780 inches single mounting facility single center group and 2.840 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.690 inches single mounting facility single center group and 2.810 inches single mounting facility single center group

Mounting Slot Width:

0.180 inches single group

Frequency Rating:

47.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

3.375 inches

Body Width:

3.500 inches

Body Height:

2.810 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

3.75 amperes dc single component 1st secondary

Winding Operating Voltage:

35.00 dc volts single component 1st secondary

Special Features:

Secondary voltages are after rectification

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0