## NSN 5950-01-072-3976

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-072-3976
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.780 inches single mounting facility single center group and 2.840 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.690 inches single mounting facility single center group and 2.810 inches single mounting facility single center group
Mounting Slot Width:
0.180 inches single group
Frequency Rating:
47.0 hertz single component and 63.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to core single component
Body Length:
3.375 inches
Body Width:
3.500 inches
Body Height:
2.810 inches
Inclosure Type:
Open
Mounting Facility Quantity:
4 single group
Mounting Method:
Slot single group
Winding Function And Quantity:
1 primary single component and 2 secondary single component
Winding Operating Current:
3.75 amperes dc single component 1st secondary
Winding Operating Voltage:
35.00 dc volts single component 1st secondary
Special Features:
Secondary voltages are after rectification
Terminal Type And Quantity:
8 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

## NSN 5950-01-072-3976

Power Transformer - Page 2 of 2



Fiig:

A058b0