

View Online at <https://aerobasegroup.com/nsn/5950-01-074-8721>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Fungus resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.850 inches single mounting facility single center group

Mounting Slot Width:

0.112 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.880 inches

Body Width:

3.750 inches

Body Height:

4.620 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Winding Operating Current:

40.0 milliamperes ac single component 4th secondary

Winding Operating Voltage:

45.00 ac volts single component 2nd secondary

Test Data Document:

97384-52721-90012 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

13 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0