

View Online at <https://aerobasegroup.com/nsn/5950-01-076-3961>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.812 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Mounting Hole Diameter:

0.187 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component and three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta

Maximum Transformer Power Rating:

291.9 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

4.750 inches

Body Width:

2.500 inches

Body Height:

4.000 inches

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 12 secondary single component

Winding Operating Current:

81.0 milliamperes ac single component 2nd secondary

Winding Power Rating:

7.0 volts-amperes single component 1st secondary

Winding Operating Voltage:

196.00 ac volts single component single primary

Special Features:

One primary winding; twelve secondary windings

Terminal Type And Quantity:

39 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0